SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name PT Maintenance Paste Product no. 11 REACH registration number Not applicable Other means of identification

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Woodoil The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

NOWOCOAT INDUSTRIAL A/S Gl. Donsvej 6 6000 Kolding tlf: +45 75 50 11 11 mail@nowocoat.dk Contact person Joen Reinert

E-mail

joen@nowocoat.dk SDS date 14-03-2013

SDS Version

1.0

1.4. Emergency telephone number

Use your national or local emergency number See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This product is not classified as dangerous. See full text of H/R-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)

Hazard statement(s)

Identity of the substances primarily responsible for the major health hazards

	General	-
Safety	Prevention	-
statement(s)	Response	-
	Storage	-
	Disposal	-

2.3. Other hazards

Additional labelling Safety data sheet available on request. Additional warnings voc

VOC-MAX: 300 g/l, MAXIMUM VOC CONTENT (Phase II, f (SB)): 700 g/l.

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances

NAME: IDENTIFICATION NOS.: CONTENT: DSD CLASSIFICATION: CLP CLASSIFICATION:	Distillates (petroleum), hydrotreated light CAS-no: 64742-47-8 EC-no: 265-149-8 Index-no: 649-422-00-2 60-80% Xn; R65 Asp. Tox. 1 H304
NAME: IDENTIFICATION NOS.: CONTENT: DSD CLASSIFICATION: CLP CLASSIFICATION:	Alkanes, C11-15-iso- CAS-no: 90622-58-5 EC-no: 292-460-6 <1% Xn;R65 R66 Asp. Tox. 1 H304, EUH066
NAME: IDENTIFICATION NOS.: CONTENT: DSD CLASSIFICATION: CLP CLASSIFICATION:	barium bis(2-ethylhexanoate) CAS-no: 2457-01-4 EC-no: 219-535-8 <1% -
NAME: IDENTIFICATION NOS.: CONTENT: DSD CLASSIFICATION: CLP CLASSIFICATION:	2-ethylhexansyre, zirconiumsalt CAS-no: 22464-99-9 EC-no: 245-018-1 <1% Xi;R38 NA
NAME: IDENTIFICATION NOS.: CONTENT: DSD CLASSIFICATION: CLP CLASSIFICATION:	cobalt bis(2-ethylhexanoate) CAS-no: 136-52-7 EC-no: 205-250-6 <1% NA

(*) See full text of H/R-phrases in chapter 16. Occupational limits are listed in section 8, if these are available.

Other informations

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the injured person into fresh air. Make sure there is always someone with the injured person. Prevent shock by keeping the injured person warm and calm. If the person stops breathing, give mouth-to-mouth resuscitation. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip. Call an ambulance.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

No special

4.3. Indication of any immediate medical attention and special treatment needed

No special Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

No special

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures No specific requirements.
- 6.2. Environmental precautions
 - No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original.

Storage temperature

NA

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

No data available DNEL / PNEC

DNEL (cobalt bis(2-ethylhexanoate)): 235 µg/m3 - Exposure: Inhalation - Duration: Long term local - Remarks: Workers DNEL (cobalt bis(2-ethylhexanoate)): 55,8 µg/kg - Exposure: Oral - Duration: long term systemic - Remarks: General population DNEL (cobalt bis(2-ethylhexanoate)): 31 µg/m3 - Exposure: Inhalation - Duration: Long term local - Remarks: General population

PNEC (cobalt bis(2-ethylhexanoate)): 0,51 µg/l - Exposure: Water - Duration: Single - Remarks: Fresh water PNEC (cobalt bis(2-ethylhexanoate)): 2,36 µg/l - Exposure: Water - Duration: Single - Remarks: Marine water

8.2. Exposure controls

No control is necessary if the product is used in a normal way.

General recommendations

Smoking, consumption of food or liquid, and storage of tobacco, food or liquid, are not allowed in the

workroom.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied. **Exposure limits**

There are no maximum exposure limits for the substances contained in this product.

Appropriate technical measures

Take ordinary precautions when using the product. Avoid inhalation of gas or dust.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Only CE-marked personal protection equipment should be used.

Respiratory Equipment

Recommended: A, Class 1 (low capacity), Brown

Skin protection

No specific requirements.

Hand protection

Recommended: Polyvinyl alcohol (PVA). . Breakthrough time: See the manufacturer's instructions Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties							
Form	Colour	Odour	pН	Viscosity	Density (g/cm3)		
Liquid	Various colours	Mild	-	-	0,8		
Phase changes							
Melting point (°C)	Boiling	Boiling point (°C)		Vapour pressure (mm Hg)			
-	-			-			
Data on fire and explosion hazards							
Flashpoint (°C)	Ignition	(°C)		Self ignition	(°C)		
100	-			-			
Explosion limits (Vol	%) Oxidizir	ng properties					
-	-						
Solubility							
Solubility in water	n-octan	ol/water coefficient	t				
Insoluble	-						
9.2. Other information							
Solubility in fat	Additio	nal information					
-	N/A						

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Do not expose to heat (e.g. sunlight), because it can lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidising agents, and strong catabolic agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects							
Acute toxicity							
Substance Alkanes, C11-15-iso- Alkanes, C11-15-iso- Alkanes, C11-15-iso- cobalt bis(2-ethylhexanoate) cobalt bis(2-ethylhexanoate) Distillates (petroleum), hydro Distillates (petroleum), hydro Distillates (petroleum), hydro Distillates (petroleum), hydro Distillates (petroleum), hydro	Species Rat Rabbit Rat Rat Rat Rat Rabbit Rat	Test LD50 LD50 LC50 LD50 LD50 LD50 LD50 LD50 LC50	Route of exposure Oral Dermal Inhalation Oral Dermal Oral Dermal Inhalation	Result >5000 mg/kg >3160 mg/kg >715 ppm 3129 mg/kg >2000 mg/kg >5000 mg/kg >2000 mg/kg >5,28 mg/l			
SECTION 12: Ecological information							
 12.1. Toxicity Substance Alkanes, C11-15-iso- Alkanes, C11-15-iso- cobalt bis(2-ethylhexanoate) cobalt bis(2-ethylhexanoate) Distillates (petroleum), hydro Distillates (petroleum), hydro Distillates (petroleum), hydro Bistillates (petroleum), hydro 12.2. Persistence and degradabi Substance Alkanes, C11-15-iso- cobalt bis(2-ethylhexanoate) Distillates (petroleum), hydro 	Species Fish Daphnia Fish Daphnia Fish Daphnia Daphnia Algae	Test LC50 EC50 LC50 EC50 LC50 NOEC EC50 EC50 EC50	Test duration 96 h 48 h 96 h 28 d 96 h 28 d 48 h 21 d 72 h Test No data available CO2 Evolution Test CO2 Evolution Test	Result 2890 mg/l <100 mg/l			
12.3. Bioaccumulative potential Substance Alkanes, C11-15-iso- cobalt bis(2-ethylhexanoate) Distillates (petroleum), hydro	Potential bioaccur No No Yes	nulation	LogPow No data available No data available 3	BFC No data available No data available No data available			

12.4. Mobility in soil

Distillates (petroleum), hydro...: Log Koc= 2,4541, Calculated from LogPow (Moderate mobility potential.). 12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

This product contains substances which can cause undesirable long-term effects in the water environment, due to its poor biodegradability. This product contains substances which can accumulate in the food chain because they are bioaccumulative substances. Bioaccumulative substances can accumulate in fat tissue and are not easily secreted.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

This product is not covered by the regulations on dangerous waste.

Waste

EWC code

Specific labelling

Contaminated packing

No specific requirements.

SECTION 14: Transport information Not listed as dangerous goods under ADR and IMDG regulations. 14.1 - 14.414.1. UN 14.4. Packing 14.3. Transport ADR/RID 14.2. UN proper shipping name Notes number hazard class(es) group Hazardous IMDG UN-no. **Proper Shipping Name** Class PG* EmS MP** constituent

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Demands for specific education

Additional information

15.2. Chemical safety assessment No

SECTION 16: Other information'

Sources

EC regulation 1907/2006 (REACH) Directive 2000/532/EC EC Regulation 1272/2008 (CLP)

Full text of H/R-phrases as mentioned in section 3

R38 - Irritating to skin.

R65 - Harmful: may cause lung damage if swallowed.

R66 - Repeated exposure may cause skin dryness or cracking.

H304 - May be fatal if swallowed and enters airways.

EUH066 - Repeated exposure may cause skin dryness or cracking.

The full text of identified uses as mentioned in section 1

Other symbols mentioned in section 2

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by Joen Reinert

Date of last essential change (First cipher in SDS version)

04-03-2013

Date of last minor change (Last cipher in SDS version) 14-03-2013

ALPHAOMEGA. Licens nr.:2827342878, Nowocoat Industrial A/S www.chymeia.com