

11. Maintenance Paste

For maintenance of oil and waxed floors in natural and white

Work Instruction:

1. Start cleaning the floor with Intensive Wood Cleaner. Mix 125ml of Intensive Wood Cleaner into 5 litres of lukewarm water. Always two buckets – one with Wood Cleaner water and one with rinsing water and leave floor to dry for 4 to 8 hours after cleaning.

2. Press a small quantity of Maintenance Paste onto the floor - enough to maintain 1 to 2 m² at the time. Buff immediately with white polishing pad under floor machine. Ensure that Maintenance Paste is buffed well into wood grain and if necessary spread to next part if excess paste appears.

3. Ensure that Maintenance Paste is buffed well into the wood grain leaving a uniformly saturated oiled surface. The surface should appear silk matt and any excess material should be transferred to next area. Continue till whole area has been maintained with Maintenance Paste.

4. Note that the Maintenance Paste is fast drying and therefore finish the application area by area. In case of sticky surface, sprinkle or spray minor quantity of Proff Woodcare Thinner.

5. Leave surface to dry for 4 hours at 18 degrees Celsius. After initial drying, the floor can be used with caution. Do not expose to water till after complete drying of Maintenance Paste.

6. Leave the oiled area to dry for 24 hours. Do not expose the floor to water during drying time.

7. Tools may be cleaned with Proff Woodcare Thinner.

8. Clean the floor regularly with Proff Woodcare Wood Floor Soap or Proff Woodcare Oil Soap.

Risk of self ignition: sanding dust and oil wetted cloths and pads must be disposed of either by soaking in water or burnt immediately after use. **Risk of self ignition.**

Disposal: Empty containers and product residue disposed of according to regional rules and regulations.

Declaration of content:

VOC content info:

Consumption: 1 litre to 200 – 250m² of floor

-
- **Storage:** Keep in tightly closed original packaging. Do not expose to heat (e.g. sunlight). Store frost-free and out the reach of children.
 - **Note!!** Please always make a test coat on the surface for controlling the compatibility
 - **Warning:** Rags, pads, or waste soaked with oil may selfignite if improperly discarded. Immediately after use, place all rags and waste in a sealed, water filled bucket for proper disposal.