

PROFF WOODCARE EXTERIOR WOOD OIL



www.proffwoodcare.com

AREAS OF APPLICATION:

Exterior Wood Oil is for finishing of any type of exterior wood – garden furniture, decking boards, fences, and cladding. Exterior Wood Oil may be used for all wood species without exceptions. Exterior Wood Oil is available in a number of colours, and we recommend choosing a colour close to the wood species in question. The combination of pigment and oil ensures a better protection of the wood and a durable finish. Exterior Wood Oil may be applied on untreated wood but also used for maintenance of the wood at a later date. The selection of oil components guarantees a durable and easy to apply material. Wood, treated with Exterior Wood Oil is water-repellent and added active fungicide protects surfaces against mould and fungus, ensuring long-term durability. Furthermore, the Exterior Wood Oil has a built-in UV-filter protecting the wood from the damaging rays from the sun.

APPLICATION OF MATERIAL:

1. Clean the wood work with Exterior Wood Cleaner carefully before application of the oil. Make sure that the woodwork is completely dry before starting the application of the oil. Moisture in wood should not exceed 15% relative moisture content. Application should be made in dry weather with low humidity.
2. Stir the container well and ensure that all pigments are evenly distributed in material before application.
Apply the oil in dry weather and do not apply in direct sunlight. Apply 1 litre of oil to 10 to 15 m² of wood work with a paint brush in a thin layer. Let the oil penetrate the wood grain for up to 15 min. and if dry spots appear, reapply oil. Now work the oil into the wood grain with pad or pad mounted under floor machine in case of decking boards. Any excess oil is removed from surface with cotton cloths.
3. When the oil is dry after 24 hours, the woodwork may need buffing with polishing pad to smoothen the surface. 5. If surface was extremely over grown with dirt, a second cleaning may be necessary. Repeat process under point 2.

BANGKIRAI
LARCH
NATUR
OLIVE
SILVER
TEAK
WALNUT



PROFF WOODCARE EXTERIOR WOOD OIL



www.proffwoodcare.com

MAINTENANCE

It is recommended to apply oil for maintenance whenever the finish seems to lack lustre. First clean the woodwork with Exterior Wood Cleaner and follow the instruction above for work process.

CONSUMPTION

1 litre 10 – 15m² of woodwork.

RISK OF SELF IGNITION:

Sanding dust and oil wetted cloths and pads should be disposed of either by soaking in water or burnt immediately after use. Risk of self ignition.

WARNING

Rags, pads, or waste soaked with oil may selfignite if improperly discarded. Immediately after use, place all rags and waste in a sealed, water filled bucket for prober disposal.

DISPOSAL

Empty containers and product residue disposed of according to regional rules and regulations.

STORAGE

Keep in tightly closed original packaging. Do not expose to heat (e.g. sunlight). Store frost-free and out the reach of children.

DECLARATION OF CONTENT

Natural Oil components.

NOTE!

Please always make a test on the surface for controlling the compatibility

VOC CONTENT INFO:

VOC-Max: 20 g/l, Maximum VOC content (Phase II, f (OB)): 700 g/l.

