

PROFF WOODCARE CLEANING OIL



www.proffwoodcare.com

AREAS OF APPLICATION:

Cleaning Oil is suitable for use on all pre-oiled interior floors and woodwork in general. It brings back the lustre to the oiled surface and makes it harder wearing and more resistant to stains after every application. Cleaning Oil may be applied by hand or with a floor machine.

WORK INSTRUCTION

1. Make sure that the floor or woodwork is freshly cleaned with Intensive Wood Cleaner. Ensure that the floor is completely dry before starting the application of the oil.

2. Shake the bottle and if white oil, ensure that all white pigments are evenly distributed in material before application. Apply 1 litre of oil to 30 to 40 m² of floor possibly with spray bottle. Now work the oil inside wood grain with floor machine mounted with white pad or by hand with white pad.

3. If not all oil could be worked into the wood grain, scrape the excess oil onto the next section of the floor or remove with cotton cloths. Continue in this way until complete area has been coated.

4. Now buff the complete area with a white pad under floor machine or by hand.

5. After a 4 hour pre-drying of the area, if the oil was buffed in with floor machine, you may use the floor with caution. If applied by hand, wait 8 hours before using the floor with caution.

6. Leave the oiled area to dry for 24 hours. Do not expose the floor to water during drying time. Cover walkways with corrugated paper.

7. Use Proff Woodcare Wood Floor Soap mixed with water for regular cleaning. For intermediate re-oiling, Oil Refresher mixed with water is also an option.



PROFF WOODCARE WOOD LYE



www.proffwoodcare.com

Risk of self ignition: Sanding dust and oil wetted cloths and pads must be disposed of either by soaking in water or burnt immediately after use.

Disposal: Empty containers and product residue disposed of according to regional rules and regulations.

Declaration of content: Natural oil components.

VOC content info: VOC-MAX: 20 g/l, MAXIMUM VOC CONTENT (Phase II, f (SB)): 700 g/l.

Consumption: 1 litre to 30 – 40m² of woodwork

Storage: Keep in tightly closed original packaging. Do not expose to heat (e.g. sunlight). Store frostfree and out of the reach of children.

Note!! Please always make a test on the surface for controlling the compatibility

Warning: Rags, pads, or waste soaked with oil may selfignite if improperly discarded. Immediately after use, place all rags and waste in a sealed, water filled bucket for proper disposal.

Classification of the substance or mixture: This product is not classified as dangerous.