

PROFF WOODCARE GARDEN FURNITURE OIL



www.proffwoodcare.com

AREAS OF APPLICATION:

Proff Garden Furniture Oil Spray is generally used for maintenance of garden furniture but may also be used for basic treatment. The oil ensures a hard wearing and water repellent surface. It is especially developed and offers also a UV filter for protection of deteriorating rays from the sun. Garden Furniture Oil may be used for all exterior wood work which needs to be maintained.

WORK INSTRUCTION

1. Clean the garden furniture with Proff Exterior Wood Cleaner carefully before spraying the oil. Make sure that the garden furniture is completely dry before starting the application of the oil. Moisture in wood should not exceed 15% relative moisture content. Application should be made in dry weather with low humidity.
2. Shake the container well and ensure that all components are evenly distributed in material before application. Spray the oil in dry weather and do not apply in direct sunlight. Maintain with Garden Furniture Oil when necessary. Let the oil penetrate the wood grain for up to 15 min. and if dry spots appear, reapply oil. Now work the oil into the garden furniture with pad.
3. When the oil is dry after 24 hours, the garden furniture may need buffing with polishing pad to smoothen the surface.



PROFF WOODCARE GARDEN FURNITURE OIL



www.proffwoodcare.com

Risk of self ignition: Sanding dust and oil wetted cloths and pads should be disposed of either by soaking in water or burnt immediately after use. Risk of self ignition.

Disposal: Empty containers and product residue disposed of according to regional rules and regulations.

Consumption: 1 litre to 15 – 20m² of woodwork

Storage: Keep in tightly closed original packaging. Do not expose to heat (e.g. sunlight). Store frostfree and out the reach of children.

Note!! Please always make a test coat on the surface for controlling the compatability

Warning: Rags, pads, or waste soaked with oil may selfignite if improperly discarded. Immediately after use, place all rags and waste in a sealed, water filled bucket for prober disposal.