

PROFF WOODCARE ISOFIN SOAP WITH WAX



www.proffwoodcare.com

AREAS OF APPLICATION:

Isofin Soap with Wax – natural and white are based on effective tree soaps, added wax, surface actives and titan white. The mixture makes the product very effective for cleaning and for letting it into the pores and surface of the tree, which provides the tree with an effective protection against coffee, red wine, grease etc. Isofin Soap with Wax provides the tree with a surface, looking silky mat and easy to clean. Isofin Soap with Wax is a pure and friendly product to the environment.

WORK INSTRUCTION

Isofin Soap with Wax is especially made for after treatment and daily cleaning of lye treated or oiled tree on floors, furniture, doors etc. It is also qualified for old lye treated or untreated tree that needs to be refreshed. The soap can also be used for new or new grinded tree. Isofin Soap with Wax, natural or white, is used, depending on how light a result you want.

Isofin Soap with Wax natural is typically used for dark tree sorts (mahogany, teak, cherry etc) whilst the Isofin Soap with Wax white typically is used for light tree sorts and/or lye treated tree (beech, pine, ash, oak etc) The soap can be applied 1 hour after the lay treatment.

1. Lye treated tree must be filled with a fat combination of Isofin Soap with Wax and water:1 part of soap to 10 parts of water.
2. The tree must be washed in length direction with a rag or floor cloth.



PROFF WOODCARE ISOFIN SOAP WITH WAX



www.proffwoodcare.com

MAINTENANCE:

The daily maintenance and cleaning process of tree treated with Isofin Soap with Wax is simply vacuuming. When the tree starts to take dirt, it is easy to wash with the Isofin Soap with Wax as above mentioned.

Very dirty tree or spots are washed away with tree cleaner and then treated with Isofin Soap with Wax.

Disposal: Empty containers and product residue disposed of according to regional rules and regulations.

Consumption: 20-60 m² per litre by 1 part soap to 10 liters of water.

Storage: Keep in tightly closed original packaging. Do not expose to heat (e.g. sunlight). Store frost-free and out the reach of children.

Note!! Please always make a test coat on the surface for controlling the compatibility